



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
GHS: The Globally Harmonized System of Classification and Labeling of Chemicals

BOSTIK SIMSON PREP G PLUS
Revision Number 2.02

Revision date 11-Jan-2022
Supersedes Date: 16-Jun-2021

Section 1: Identification

Product identifier

Product Name BOSTIK SIMSON PREP G PLUS

Other means of identification

Recommended use of the chemical and restrictions on use

Recommended use Adhesive

Uses advised against Consumer use

Details of the supplier of the safety data sheet

Supplier

Bostik New Zealand Limited
19 Eastern Hutt Road Wingate,
Lower Hutt, New Zealand
Tel: 04-567 5119
Fax: 04-567 5412

E-mail address SDS.AP@Bostik.com

Emergency telephone number

Emergency Telephone 24 Hr: 0800 243 622
+64 4 917 9888
Poison Centre : 0800 764 766

Section 2: Hazard identification

GHS Classification

Flammable liquids	Category 2 (HSNO - 3.1B)
Serious eye damage/eye irritation	Category 2 (HSNO - 6.4A)
Respiratory sensitization	Category 1 (HSNO - 6.5A)
Skin sensitization	Category 1 (HSNO - 6.5B)
Carcinogenicity	Category 2 (HSNO - 6.7B)
Specific target organ toxicity (single exposure)	Category 3 (HSNO - 6.9B)

Label elements



Signal word
Danger

Hazard statements
H225 - Highly flammable liquid and vapor

SAFETY DATA SHEET

BOSTIK SIMSON PREP G PLUS
Revision Number 2.02

Revision date 11-Jan-2022
Supersedes Date: 16-Jun-2021

H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/protective clothing/eye protection/face protection
Wash face, hands and any exposed skin thoroughly after handling
Avoid breathing dust/fume/gas/mist/vapors/spray
In case of inadequate ventilation wear respiratory protection
Contaminated work clothing should not be allowed out of the workplace
Use only outdoors or in a well-ventilated area
Ground and bond container and receiving equipment
Use non-sparking tools
Take action to prevent static discharges
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Keep cool
Use explosion-proof electrical/ ventilating/ lighting/ equipment

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Skin

If skin irritation or rash occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]

Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

If experiencing respiratory symptoms: Call a POISON CENTER or doctor

Fire

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards which do not result in classification

In use, may form flammable/explosive vapor-air mixture.

Section 3: Composition/information on ingredients

Chemical name	CAS No	Weight-%
Methyl ethyl ketone	78-93-3	40 - <80
Carbon black	1333-86-4	10 - <20
4,4'-Methylenediphenyl diisocyanate	101-68-8	0.1- <1
Isophorone diisocyanate	4098-71-9	0.1- <1

Non-hazardous ingredients	Proprietary	Balance
---------------------------	-------------	---------

Section 4: First-aid measures

Description of first aid measures

SAFETY DATA SHEET

BOSTIK SIMSON PREP G PLUS
Revision Number 2.02

Revision date 11-Jan-2022
Supersedes Date: 16-Jun-2021

General advice	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.
Inhalation	May cause allergic respiratory reaction. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Get immediate medical advice/attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
Ingestion	May produce an allergic reaction. Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

Most important symptoms and effects, both acute and delayed

Symptoms	May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/or wheezing. Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Note to physicians	May cause sensitization in susceptible persons. Treat symptomatically.
---------------------------	--

Section 5: Fire-fighting measures

Hazchem code	•3YE
---------------------	------

Suitable Extinguishing Media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
-------------------------------------	---

Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
-------------------	--

Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
---------------------------------------	---

Specific hazards arising from the chemical

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitizer. May cause sensitization by inhalation and skin contact. May cause sensitization by skin contact.
---	---

Hazardous combustion products	Carbon oxides. Carbon monoxide. Carbon dioxide (CO ₂).
--------------------------------------	--

Special protective actions for fire-fighters

Special protective equipment and	Firefighters should wear self-contained breathing apparatus and full firefighting turnout
---	---

SAFETY DATA SHEET

BOSTIK SIMSON PREP G PLUS
Revision Number 2.02

Revision date 11-Jan-2022
Supersedes Date: 16-Jun-2021

precautions for fire-fighters gear.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage

Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Provide extract ventilation to points where emissions occur. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash before reuse.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

Conditions for safe storage, including any incompatibilities

SAFETY DATA SHEET

BOSTIK SIMSON PREP G PLUS
Revision Number 2.02

Revision date 11-Jan-2022
Supersedes Date: 16-Jun-2021

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children.
Recommended storage temperature	Keep at temperatures between 41 and 77 °F / 5 and 25 °C.
Incompatible materials	None known based on information supplied.

Section 8: Exposure controls/personal protection

Control parameters

Exposure Limits This product contains carbon black in a non-respirable form. Inhalation of carbon black is unlikely to occur from exposure to this product.

Chemical name	New Zealand	ACGIH TLV	United Kingdom	Australia
Methyl ethyl ketone 78-93-3	TWA: 150 ppm TWA: 445 mg/m ³ STEL: 300 ppm STEL: 890 mg/m ³	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 899 mg/m ³ Sk*	150 ppm TWA 445 mg/m ³ TWA 300 ppm STEL 890 mg/m ³ STEL
Carbon black 1333-86-4	TWA: 3 mg/m ³	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³	3 mg/m ³ TWA
4,4'-Methylenediphenyl diisocyanate 101-68-8	TWA: 0.02 mg/m ³ STEL: 0.07 mg/m ³	TWA: 0.005 ppm	TWA: 0.02 mg/m ³ STEL: 0.07 mg/m ³	0.02 mg/m ³ TWA 0.07 mg/m ³ STEL
Isophorone diisocyanate 4098-71-9	TWA: 0.02 mg/m ³ STEL: 0.07 mg/m ³ Skin	TWA: 0.005 ppm	TWA: 0.02 mg/m ³ Capable of causing occupational asthma	0.02 mg/m ³ TWA 0.07 mg/m ³ STEL

Biological occupational exposure limits This product contains carbon black in a non-respirable form. Inhalation of carbon black is unlikely to occur from exposure to this product.

Chemical name	New Zealand	ACGIH
Methyl ethyl ketone 78-93-3	2 mg/L - urine (MEK) - end of shift	2 mg/L - urine (MEK) - end of shift
4,4'-Methylenediphenyl diisocyanate 101-68-8	10 µg/g creatinine - urine (4,4-Diaminodiphenyl) - end of shift or end of work week	-

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection	Tight sealing safety goggles.
Hand protection	Wear suitable gloves. Impervious gloves.
Skin and body protection	Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

SAFETY DATA SHEET

BOSTIK SIMSON PREP G PLUS
Revision Number 2.02

Revision date 11-Jan-2022
Supersedes Date: 16-Jun-2021

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Dispersion
Color	Black
Odor	Solvent.
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	Not applicable Insoluble in water
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	80 °C	
Flash point	-10 °C	
Evaporation rate	No data available	None known
Flammability	Not applicable for liquids .	
Flammability Limit in Air		None known
Upper flammability or explosive limits	11.5 % (V)	
Lower flammability or explosive limits	0.8 % (V)	
Vapor pressure	150	hPa
Relative vapor density	2.5	
Relative density	0.95	
Water solubility	No data available	Insoluble in water
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	400 °C	
Decomposition temperature		None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No information available.	
Oxidizing properties	No information available.	

Other information

Softening Point	No information available
Molecular weight	No information available
VOC Content (%)	66.89
Density	No information available
Bulk density	No information available
Particle characteristics	

Section 10: Stability and reactivity

Reactivity

Reactivity No information available.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

SAFETY DATA SHEET

BOSTIK SIMSON PREP G PLUS
Revision Number 2.02

Revision date 11-Jan-2022
Supersedes Date: 16-Jun-2021

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Hazardous polymerization Hazardous polymerization may occur.

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks.

Incompatible materials

Incompatible materials None known based on information supplied.

Hazardous decomposition products

Hazardous decomposition products Carbon monoxide. Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Hydrogen cyanide. Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Section 11: Toxicological information

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause sensitization in susceptible persons. (based on components). May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause sensitization by skin contact. May cause irritation. Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. May cause additional affects as listed under "Inhalation". Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-dust/mist) 6.33 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl ethyl ketone	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus cuniculus)	=11700 ppm (Rattus) 4 h

SAFETY DATA SHEET

BOSTIK SIMSON PREP G PLUS
Revision Number 2.02

Revision date 11-Jan-2022
Supersedes Date: 16-Jun-2021

Carbon black	LD50 > 8000 mg/kg (Rattus) OECD 401	> 3 g/kg (Oryctolagus cuniculus)	> 4.6 mg/m ³ (Rat) 4 h
4,4'-Methylenediphenyl diisocyanate	=31600 mg/kg (Rattus) = 9200 mg/kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus) OECD 402	=1.5 mg/L (Rattus) 4 h
Isophorone diisocyanate	=4814 mg/kg (Rattus)	LD50 > 2000 mg/kg	=0.135 mg/L (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Component Information
Methyl ethyl ketone (78-93-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

4,4'-Methylenediphenyl diisocyanate (101-68-8)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye	0.1 mL	24 hours	Non-irritant

Respiratory or skin sensitization May cause sensitization by inhalation. May cause sensitization by skin contact.

Methyl ethyl ketone (78-93-3)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitization	Guinea pig	Dermal	No sensitization responses were observed

4,4'-Methylenediphenyl diisocyanate (101-68-8)

Method	Species	Exposure route	Results
OECD GD 39	Rat	Inhalation	Sensitizing

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. Suspected of causing cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	New Zealand	IARC
Carbon black - 1333-86-4	Suspected carcinogen	Group 2B
4,4'-Methylenediphenyl diisocyanate - 101-68-8	-	Group 3

Legend

IARC (International Agency for Research on Cancer)
Group 2B - Possibly Carcinogenic to Humans
Group 3 - Not Classifiable as to Carcinogenicity in Humans

4,4'-Methylenediphenyl diisocyanate (101-68-8)

Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Limited evidence of a carcinogenic effect

Reproductive toxicity Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

BOSTIK SIMSON PREP G PLUS
Revision Number 2.02

Revision date 11-Jan-2022
Supersedes Date: 16-Jun-2021

STOT - single exposure May cause drowsiness or dizziness. May cause respiratory irritation. Classification based on data available for ingredients.

Respiratory irritation No information available.

Narcotic effects Narcotic effects.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Section 12: Ecological information

Ecotoxicity

Ecotoxicity

Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Crustacea
Methyl ethyl ketone	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	EC50 48 h > 308 mg/L (Daphnia magna)
Carbon black	>10000 mg/l (Desmodesmus subspicatus) OECD 202	>1000 mg/l (Brachydanio rerio) OCDE 203	EC50: >5600mg/L (24h, Daphnia magna)
4,4'-Methylenediphenyl diisocyanate	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	>1000 mg/l (Danio rerio)	EC50 (24H) >1000 mg/L Daphnia magna
Isophorone diisocyanate	EC50: =118.7mg/L (72h, Desmodesmus subspicatus)	LC50: =1.8mg/L (48h, Leuciscus idus)	EC50: =83.7mg/L (24h, Daphnia magna)

Terrestrial ecotoxicity There is no data for this product.

Persistence and degradability No information available.

Methyl ethyl ketone (78-93-3)

Method	Exposure time	Value	Results
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	biodegradation	98 % Readily biodegradable

4,4'-Methylenediphenyl diisocyanate (101-68-8)

Method	Exposure time	Value	Results
OECD Test No. 302C: Inherent Biodegradability: Modified MITI Test (II)	28 days	0% biodegradation	Not readily biodegradable

Isophorone diisocyanate (4098-71-9)

Method	Exposure time	Value	Results
EU C.4-D	28 days	0%	Not readily biodegradable

Bioaccumulative potential

Bioaccumulation There is no data for this product.

SAFETY DATA SHEET

BOSTIK SIMSON PREP G PLUS
Revision Number 2.02

Revision date 11-Jan-2022
Supersedes Date: 16-Jun-2021

Component Information

Chemical name	Partition coefficient
Methyl ethyl ketone	0.3
4,4'-Methylenediphenyl diisocyanate	4.51

Mobility in soil

Other adverse effects

No information available.

Section 13: Disposal considerations

Disposal methods

Waste from residues/unused products

Dispose of product in packaging in a way that is consistent with the EPA Consolidation 30 April 2021 of the Hazardous Substances (Disposal) Notice 2017 and the Act. Treat the substance using a method that changes the characteristics or composition of the substance so that the substance is no longer a hazardous substance; or export the substance from New Zealand as waste. Flammable substances - may not be disposed of into or onto a landfill or sewage facility.

They may only be burnt in certain situations.

Flammable gases, liquids and solids may only be discharged into the environment or landfill as waste if the substance will not at any time come into contact with any explosives, oxidising gases, liquids or solids or organic peroxides; and there will be no ignition source in the vicinity of the disposal site at any time and if the substance were to ignite, no person, or place where a person may legally be, would be exposed to an unsafe level of heat radiation. Substances which are hazardous to human health or corrosive to metals – may be discharged into the environment if a tolerable exposure limit has been set for the substance (or a component of that substance); and the discharge does not, after reasonable mixing, result in the concentration of the substance in an environmental medium exceeding the tolerable exposure limit. If there is no tolerable exposure limit for the substance, then it may only be discharged into the environment if the substance is very rapidly converted to substances that are not hazardous substances.

Contaminated packaging

For packages that have been in direct contact with hazardous substances, the person must ensure that the package is rendered incapable of containing any substance. It must be disposed of in a manner that is consistent with the requirements for disposal of the substance that it contained, taking into account the material the package is manufactured from. Packages may only be reused or recycled if:

- the substance has a physical hazard other than corrosive to metal, and has been treated to remove any residual contents of the hazardous substance;
- or for substances that have a health or environmental hazard, or corrosive to metal, the contents of the residue in the package are below the threshold for the substance to be classified as hazardous in the Hazardous Substances (Hazard Classification) Notice 2020.

Section 14: Transport information

Hazchem code	•3YE
IATA	
UN number or ID number	UN1139
UN proper shipping name	Coating solution
Transport hazard class(es)	3
Packing group	II
Special Provisions	A3
Description	UN1139, Coating solution, 3, II

IMDG

SAFETY DATA SHEET

BOSTIK SIMSON PREP G PLUS
Revision Number 2.02

Revision date 11-Jan-2022
Supersedes Date: 16-Jun-2021

UN number or ID number UN1139
UN proper shipping name Coating solution
Transport hazard class(es) 3
Packing group II
EmS-No F-E, S-E
Marine pollutant NP
Description UN1139, Coating solution, 3, II, (-10°C c.c.)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
No information available

ADR

UN number or ID number UN1139
Proper Shipping Name Coating solution
Transport hazard class(es) 3
Labels 3
Packing group II
Description UN1139, Coating solution, 3, II, (D/E)
Limited quantity (LQ) 5 L
Special Provisions 640C
Classification code F1
Tunnel restriction code (D/E)

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

New Zealand

ERMA Group

HSR002662

Chemical name	New Zealand HSNO Chemical Classification
Methyl ethyl ketone - 78-93-3	- 3.1B,6.1E (All),6.1E (O),6.3B,6.4A,6.9B (All),6.9B (I) (HSR001190) >50% in a non hazardous diluent - 3.1B,6.1E (All),6.1E (O),6.3B,6.4A,6.9B (All),6.9B (I) (HSR007378)
Carbon black - 1333-86-4	- 6.3B,6.4A,6.7B (HSR002801) >10% in a non hazardous diluent - 6.3B,6.4A,6.7B (HSR006615)
4,4'-Methylenediphenyl diisocyanate - 101-68-8	- 6.1B (I),6.1B (All),6.1E (O),6.3A,6.4A,6.5A,6.5B,6.7B,6.9A (All),6.9A (I) (HSR003218) >7.4-37% in a non hazardous diluent - 6.1D (All),6.1D (I),6.3A,6.4A,6.5A,6.5B,6.7B,6.9A (All),6.9A (I) (HSR006535)
Isophorone diisocyanate - 4098-71-9	- 6.1C (I),6.1C (All),6.1D (O),6.1E (D),6.3A,6.4A,6.5A,6.5B,9.1D (All),9.1D (F),9.1D (C),9.1D (A),9.3C (HSR003947) >3-9% in a non hazardous diluent - 6.3B,6.5A,6.5B,9.1C (All),9.1C (F),9.1C (C),9.1C (A) (HSR005300) >1-3% in a non hazardous diluent - 6.3B,6.5A,6.5B (HSR005299)

National regulations

There are no applicable tolerable exposure limits or environmental exposure limits according to the EPA Controls for Hazardous Substances

SAFETY DATA SHEET

BOSTIK SIMSON PREP G PLUS
Revision Number 2.02

Revision date 11-Jan-2022
Supersedes Date: 16-Jun-2021

Certified handlers, tracking and controlled substance license requirements

Certified handlers are required for some substances. This includes substances requiring a controlled substance license, and most explosives, vertebrates toxic agents, and certain fumigants. Acutely toxic substances which are a Category 1 or 2, such as pesticides also require Certified handlers. Please check the Health and Safety at Work Act 2015 for further information
Tracking is required for some highly hazardous substances. These substances need to be under the control of an appropriately trained person or appropriately secured. Please check the Health and Safety at Work Act 2015 for further information
Controlled substance licenses are required to possess certain explosives, vertebrate toxic agents and fumigants. See Part 7 of the Health and Safety at Work Regulation 2017 for more information

EPA New Zealand HSNO approval code or group standard

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Section 16: Other information

Prepared By Product Safety & Regulatory Affairs
Revision date 11-Jan-2022

Revision Note

SDS sections updated. 3. 8.

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Key literature references and sources for data used to compile the SDS

EPA (Environmental Protection Agency)
International Uniform Chemical Information Database (IUCLID)
Japan GHS Classification
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
World Health Organization

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet